•5-25. The copper pipe has an outer diameter of 2.50 in. and an inner diameter of 2.30 in. If it is tightly secured to the wall at C and it is subjected to the uniformly distributed torque along its entire length, determine the absolute maximum shear stress in the pipe. Discuss the validity of this result.

•5–25. The copper pipe has an outer diameter of 2.50 in. and an inner diameter of 2.30 in. If it is tightly secured to the wall at C and it is subjected to the uniformly distributed torque along its entire length, determine the absolute maximum shear stress in the pipe. Discuss the validity of this result.

We mon

$$T = \frac{T}{J} \Rightarrow T = \frac{R}{J} \times T, \quad T is internal Torque$$

Keeping R&J constant, TXT



125 lb-ft/ft

4 in.

9 in.

12 in.

| This problem was solved by Civil Thinking (<u>https://civilthinking.com</u>) |
|--|
| If you need solutions for Strength of Materials or any |
| other Civil Engineering subject, contact us at: |
| solutions@civilthinking.com |
| Or submit your problem directly here: |
| https://civilthinking.com/getproblemsolutions |
| Other Subjects We Cover: |
| Structural Analysis |
| Fluid Mechanics |
| Geotechnical Engineering |
| Transportation Engineering |
| Construction Management |
| Finite Element Analysis (FEA) |
| |

Engineering Software (ANSYS, ETABS, MATLAB, Revit)

Let us help you solve your engineering challenges! 🜮